



Spartan Chemical Company, Inc.

## Letter of Guarantee: SPARCLEAN DETERGENT II [49]

Spartan Chemical Company, Inc., as the manufacturer of SparClean Detergent II [49], guarantees that this product is safe and effective for use in food processing plants, including federally inspected facilities, when used as directed on the product labeling and as directed below in this letter. When used in this manner this product will not adulterate food product or create unsanitary conditions. SparClean Detergent II [49] is a liquid all temperature warewash detergent for use in automatic dishwash machines.

When requested by the Canadian Food Inspection Agency (CFIA), Spartan Chemical Company, Inc., will provide all supporting documents to demonstrate that the product is safe and/or suitable for use as intended.

### **SparClean Detergent II [49]: Complies with the Following USA Requirements:**

- Complies with the Federal Food, Drug and Cosmetic Act.
- Conforms to Food Safety and Inspection Service (FSIS)'s "**Sanitation Performance Standards Compliance Guide**"
- Meets the profile of USDA's former "A2" "Compounds for use as a cleaner in soak tanks or with steam or mechanical cleaning devices in all departments".

Before using SparClean Detergent II [49], food products and packaging materials must be removed from the area or carefully protected. After using this product, surfaces must be thoroughly rinsed with potable water.

### **Directions for use:**

1. Scrape and pre-rinse dishes before washing.
2. Properly rack and load dishes according to machine manufacturer's directions.
3. SparClean Detergent II may be used with a probe or probeless dispenser. Set dispenser according to the manufacturer's directions.
4. **For Low Temperature Dish Machines:**
  - a. Charge tank with 6 – 8 ml of this product per 4 liters of water.
  - b. Titrate wash water alkalinity to verify proper chemical dosage:  
**Light Soil Load:** 6 drops (60 ppm); **Medium Soil Load:** 8 drops (80 ppm); **Heavy Soil Load:** 10 drops (100 ppm)
5. **For High Temperature Dish Machines:**
  - a. Charge tank with 8 – 14 ml of this product per 4 liters of water.
  - b. Titrate wash water alkalinity to verify proper chemical dosage:  
**Light Soil Load:** 10 drops (100 ppm); **Medium Soil Load:** 12-13 drops (120-130 ppm); **Heavy Soil Load:** 15 drops (150 ppm)

Carefully read and follow all statements on the labeling and Safety Data Sheet while using this product.

SPARTAN CHEMICAL COMPANY, INC.

Rebecca S. Kaufold  
Manager of Government Affairs & Sustainability

Issued:

This letter of guarantee is valid until the edition is replaced or revoked by Spartan Chemical. The status of this letter of guarantee may be verified by contacting Spartan Chemical Company Customer Service at 800-537-8990.

©SCC09/19

**We make clean simple**