



XTREME

Low pH Presoak



Xtreme Low pH Presoak can be used as a primary presoak, or as part of a 2-part presoak process to neutralize Xtreme High pH Presoak in preparation for conditioners and polishes. Effective on mineral and scale deposits, brake dust, and other inorganic soils, Low pH Presoak can be applied through an arch or manually using a spray wand. Recommended for use in conveyor or in-bay automatic wash systems; great for friction or touch-free.

XTREME LOW PH PRESOAK

FEATURES & BENEFITS

- Economical: Highly concentrated formula delivers low cost per car
- Convenient: Effective for conveyor or in-bay automatics
- Versatile: Can be applied through an arch or manually through a spray wand
- Efficient: Quickly breaks up mineral scale, brake dust, and other inorganic soils, preparing car for wash process
- Formulated with worker and vehicle safety in mind

RESPONSIBLE CHEMISTRY

- APE/NPE free
- Hydrofluoric acid free

SPECIFICATION DATA

| | |
|-------------------------------------|-----------------------------|
| Dilution | Refer to directions for use |
| pH | < 1.0 |
| Color | Pink |
| Fragrance | None |
| Specific Gravity @ 24°C/75°F | 1.077 |
| Density | 8.96 lbs./gal. |
| Solvents | None |
| Miscibility | Miscible in water |
| Stability: Shelf @ 24°C/75°F | 1 year minimum |
| Stability: Accelerated @ 49°C/120°F | 30 days minimum |
| Stability: Freeze/Thaw | Will withstand 3 cycles |


DIRECTIONS FOR USE

When choosing metering tips, due to water pressure and tube length the actual dilution of applied chemical may vary from the tip selected. To accurately determine dilution rate, use either volumetric or chemical titration testing.

USAGE

Dilute at 128:1–64:1 depending on seasonality, water and cleaning conditions, and car wash type.

ORDERING INFORMATION



ADDITIONAL RESOURCES

Scan the QR code to access this product's safety information and documentation.



SAFETY: For institutional and industrial use only. Be sure to read all directions, precautionary and first aid statements on product labels before using this or any other Spartan product. If questions remain, consult your employer or a physician. Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor and at www.spartanchemical.com. Workplace labels are available in English, Spanish, and French.

GUARANTEE: Spartan's modern manufacturing and laboratory control ensures uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within 12 months of the date of manufacture.