



CONTEMPO V[®]

extraction cleaner for stain resistant carpet

Contempo V is a concentrated extraction carpet cleaner. It is a light blue liquid with a fresh floral fragrance.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, OH 43537
1-800-537-8990
www.spartanchemical.com

EXTRACTION CLEANER FOR STAIN RESISTANT CARPET:

Contempo V is designed to conform with manufacturers' recommendations for stain resistant carpet. Low foaming, anionic detergents are the foundation of Contempo V. These anionic detergents actually increase the negative electrostatic field between soil and stain resistant carpet fibers, resulting in quick, effective removal of soil. Any remaining residue dries to a crystal and is easily vacuumed away. The stain resistant treatment remains intact. Carpet is clean, deodorized and free of residue which contributes to rapid resoiling.

WILL NOT INTERFERE WITH STAIN RESISTANT PROPERTIES:

Special organic sequestering compounds in the Contempo V formula combat the adverse effects of hard water on stain resistant carpeting. It contains no anti-static inhibitors, defoamers or carpet protecting agents that may interfere with the carpet's stain resistant properties.

VARIABLE DILUTIONS:

Contempo V features a dilution ratio based on the degree of soil that needs removing. Light to heavy soil as well as pre-spray spotting can be removed with Contempo V.

	Dilution	Oz./Gal.
Light Soil	1:128	1 oz.
Moderate Soil	1: 64	2 oz.
Heavy Soil	1: 40	3 oz.
Pre-spray & Spot Removal	1:12	10 oz.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

Extraction Method:

1. Remove furniture from area to be cleaned.
2. Thoroughly dry vacuum carpeting.
3. Pre-treat traffic lanes and other heavily soiled areas using Contempo V at a 1:12 dilution (10 oz./gal. of water).
4. Clean carpet following machine manufacturer's instructions. Water temperature should not exceed 140°F. For moderate soil conditions, dilute Contempo V at a 1:64 dilution (2 oz./gal. of water). Avoid over wetting carpet. If carpeting has been previously shampooed, Spartan Defoamer should be added to the recovery tank.
5. After cleaning, brush carpet pile in one direction with carpet pile brush or shag rake.
6. Avoid walking on carpet until thoroughly dry.
7. If furniture is replaced before carpet is dry, place protective pads under legs.
8. When carpet is completely dry, vacuum thoroughly.

Rotary Spin Pad/Bonnet Cleaning:

1. Follow steps one and two from extraction method above.
2. Clean carpet following machine manufacturer's instructions. Mix 1 oz. of Contempo V per gallon of water (1:128). Spray on carpet at rate of 200-300 sq. ft. per. gallon.
3. Change rotary pad frequently.
4. For best results, extract with clear water rinse or periodically deep clean using Contempo V extraction method.

NOTE: It is recommended that carpet be tested with Contempo V at a 1:64 dilution (2 oz./gal. of water) prior to cleaning. Some materials may require special handling or application. Please reference the material safety data sheet, literature and label for additional information and specification data.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.



Distributed by:

PACKAGING

309255	55-gallon drum
309230	30-gallon drum
309215	15-gallon drum
309205	5-gallon pail
309204	1-gallon (4 per case)



WOOLSAFE approved maintenance products for wool and wool-rich products

Label copy is provided in English, Spanish and French. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Product available worldwide. For institutional and industrial use only.

© SCC 5/11 L3092