



# Glossy Black

**floor finish**

This product provides a metal interlock formula with pigment that produces a brilliant, super gloss black finish.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.  
 1110 Spartan Drive  
 Maumee, OH 43537  
 1-800-537-8990  
 www.spartanchemical.com

**DEEP, HIGH SHINE!**

Metal interlock formula in combination with pre-dispersed pigment, Glossy Black Floor Finish creates a brilliant, super gloss black finish surface.

**REINFORCED WITH URETHANE FOR EXTRA DURABILITY:**

Fortified with urethane for extra strength, Glossy Black Floor Finish is built to last even under heavy traffic conditions. Resists black heel marks, equipment skid marks, scratches and scuffs. Non-powdering.

**TIME/LABOR/MONEY SAVER:**

Smooth leveling, this user friendly floor finish is easy to apply. No buffing required. One gallon coats up to 3,000 square feet. Easy to repair. Strippable. May be used as a topcoat on existing clear finish.

**DIRECTIONS FOR USE:**

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

**INITIAL APPLICATION:**

Apply with care. May cause permanent staining. Protect hands, skin and clothing. Protect all adjacent areas and materials which should not be exposed to finish with masking tape and plastic sheeting, i.e., walls, furniture, metal fixtures, carpeting, etc. Check surfaces for tape sensitivity. Tape may remove paint, for example.

1. Completely strip all old wax or floor finish. Depending upon build-up, use warm or room temperature water (80°F - 120°F) and a Spartan Stripper.
2. Remove the stripping solution and follow with two to three clear-water rinses. Allow to dry.
3. Apply Glossy Black Floor Finish in a uniform, thin coat. Let dry for 30 minutes or until surface is completely dry to the touch. Apply subsequent coats in the same manner.

NOTE: Use Spartan Shinline Baseboard and Wax Build-up Stripper for spot clean-up.

**DAILY MAINTENANCE:**

1. Dust mop or sweep floor as necessary. Spartan water-based Dust Mop/Dust Cloth Treatment is recommended.
2. Damp mop using a Spartan neutral cleaner.
3. To easily maintain and repair traffic areas between finish applications, recoat as necessary. Can be high speed burnished.
4. For heavily soiled areas, machine scrub using the recommended dilution of Shinline Multi Surface Cleaner or Industrial Pathmaker.

**Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting [www.spartanchemical.com](http://www.spartanchemical.com).**



**SPECIFICATIONS:**

Specific Gravity (@24°C/75°F)– 1.04  
 Total Solids – 23.2%  
 Nonvolatile Solids – 18.0%  
 pH – 8.5-9.0  
 Stability  
 a. Storage (75°F) – one year  
 b. Accelerated (125°F) – 30 day minimum  
 c. Freeze/Thaw – can withstand 3 cycles  
 Gloss (Gardner)  
 a. 1 coat – 80-85  
 b. 2 coats – 95-97  
 Static coefficient of friction meets or exceeds 0.5 as determined by ASTM method D 2047.

**COVERAGE:**

Up to 3,000 square feet depending on application method and porosity of floor.



PACKAGING	
401760	275-gallon totes
401755	55-gallon drum
401730	30-gallon drum
401715	15-gallon drum
401705	5-gallon pail



Distributed by:

Label copy is available in English and Spanish. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.

For institutional and industrial use only.

© SCC 5/11 L4017