



**PREMIUM**  
**TriLinc**<sup>®</sup>

**premium high speed floor finish**

TriLinc is a premium, 25% non-volatile solids ultra performance high-speed floor finish that will not yellow or fade. Its exclusive formula is urethane fortified for extreme durability.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.  
1110 Spartan Drive  
Maumee, OH 43537  
1-800-537-8990  
www.spartanchemical.com

### REVOLUTIONARY TRIPLE LINKED POLYMER SYSTEM:

TriLinc represents leading edge Spartan technology in that it takes high speed floor finish to a completely new dimension. Most finish formulas incorporate one or two crosslinks such as, zinc salts and/or other compounds to add strength and durability to the finish. As a result, these finishes are extremely durable, but they may be prone to black heel marking and may not be easily repaired or maintained. TriLinc incorporates three crosslinks, the third of which is exclusive to Spartan...plus urethane fortification for optimum durability.

### NO AMMONIA ODOR / PLEASANT TO USE:

Unlike most traditional finishes, TriLinc contains no discernable amounts of ammonia. There are no unpleasant odors...only the hint of a cool fresh fragrance. It's the recommended complete no odor floor maintenance system for health care, supermarkets, public areas, confined spaces, anywhere people might complain about chemical odors.

### VERSATILE, TIME AND LABOR SAVING:

Use TriLinc on resilient floor, terazzo, slate, porous marble, unglazed ceramic and many other floor surfaces. Just two thin and even coats of TriLinc provides the same protection and shine of three coats of lower solids products.

### EASY TO APPLY:

TriLinc is non streaking and provides smooth, even application with no foaming, mop drag, overlapping or puddling.



Distributed by:

### DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

### APPLICATION:

**Strip:** Completely strip all old wax or floor finish. Depending upon build-up, use warm or room temperature water (80°-120°F) and a Spartan stripper. Remove the stripping solution and follow with two to three clear-water rinses. Allow to dry. Repeat if necessary.

**Seal:** Apply two coats of a Spartan sealer.

**Finish:** Apply TriLinc in uniform thin and even coat. Let dry 30 minutes or until surface is completely dry to the touch. Apply subsequent coats in the same manner.

### MAINTENANCE:

**Daily Maintenance:** Use Spartan Dust Mop/ Dust Cloth Treatment, and maintain with a Spartan neutral cleaner daily.

**Weekly Burnishing/Dry Buff:** Using a high speed pad, dry buff 2 to 3 times a week to repair minor scratches and enhance gloss.

**As Needed:** Deep scrub and recoat; or completely strip, reseal and reapply TriLinc.

**Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting [www.spartanchemical.com](http://www.spartanchemical.com).**

### SPECIFICATIONS:

Total Solids – 31.8%  
Non-Volatile Solids – 25.0%  
Specific Gravity – 1.03 @24°C/75°F  
pH (Concentrate) – 8.0 – 8.6

### Stability

- Shelf @24°C/75°F – One year minimum
- Accelerated @49°C/120°F – 30 days minimum
- Freeze/Thaw – Can withstand three cycles

### Gloss (Gardner)

- 1 coat – 92
- 2 coats – 95

Static coefficient of friction meets or exceeds 0.5 as determined by ASTM method D-2047.

### COVERAGE:

2,500 to 3,000 square feet per gallon depending on application method and porosity of floor.

### PACKAGING

403060	275-gallon totes
403055	55-gallon drum
403030	30-gallon drum
403015	15-gallon drum
403005	5-gallon pail
403004	1-gallon (4 per case)



Label copy is provided in English and Spanish.

**GUARANTEE:** Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.

For institutional and industrial use only.

© SCC 3/11 L4030