



floorFRONT™

Glossy floors with an edge!

Finally! A high gloss, low maintenance floor finish that is also environmentally responsible. Your high-traffic floors demand a superior floor finish, but budgets are lean. Enjoy measurable labor savings with FloorFront... it needs half the burnishing, recoating and stripping necessary with other zinc-free finishes.



This product meets the Green Seal™ Standard for Floor-Care Products for Industrial and Institutional Use, GS-40, based on its reduced human and aquatic toxicity and reduced smog production potential.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
 1110 Spartan Drive
 Maumee, OH 43537
 1-800-537-8990
 www.spartanchemical.com

WITH SO MANY BENEFITS, FLOORFRONT PUTS YOU ON THE FOREFRONT OF HARD FLOOR MAINTENANCE TECHNOLOGY!

You can have it all... gloss, productivity improvements, and an environmentally preferable product. FloorFront Floor Finish produces excellent off-the-mop and long-term gloss in high traffic areas – with as little as once a week burnishing. FloorFront's durable shine increases time between recoats and strip outs – without Zn crosslinking.

AN EXCEPTIONALLY DURABLE HIGH GLOSS FINISH:

A modern polymer technology formula provides for exceptional clarity, depth of gloss, and superior durability without any concern for yellowing. FloorFront will not powder with frequent burnishing and is detergent resistant.

GREEN SEAL™ CERTIFIED:



FloorFront Floor Finish meets Green Seal's GS-40 standard for industrial and institutional floorcare products based on reduced human and aquatic toxicity and reduced smog production potential. FloorFront contains no heavy metals and is completely Zinc free.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before use, read product label and MSD sheet. If questions

remain, consult your employer or a physician. **Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.**

INITIAL APPLICATION, COLD WATER IS RECOMMENDED.

1. Completely strip all old finish from floor. Depending upon build-up, use Green Solutions Floor Finish Remover.
2. Remove all stripping solution and follow with two to three clear water rinses.
3. Apply FloorFront in a uniform coat. Let dry thoroughly for 30 to 40 minutes until surface is dry to the touch. Apply subsequent coats in the same manner. Minimum three to five coats are recommended.

FloorFront is designed as a self-sealing finish.

NOTE: For best results always use Spartan floor cleaners and strippers.

MAINTENANCE:

Routine: Dust mop or sweep floor as necessary. Spartan water-based Dust Mop/Dust Cloth Treatment is recommended. Damp mop using a neutral Spartan cleaner.

Periodic Repair: Dust and damp mop per routine procedures, then dry buff or burnish using a non-aggressive polishing pad.

Yearly or as needed: For heavily soiled areas, machine scrub and re-coat or completely strip and re-finish.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATIONS:

Total Solids – 26.8 - 27.8%
 Non-Volatile Solids – 20.0%
 pH – 7.5 - 8.5

Stability:

- a. Storage @24°C/75°F – One year minimum
- b. Accelerated @49°C/120°F – 30 days minimum
- c. Freeze/Thaw -3 cycles

Gloss (Gardner) -93

Static coefficient of friction meets or exceeds 0.5 as determined by ASTM method D 2047.

COVERAGE:

2,000 to 3,000 square feet per gallon depending on application method and porosity of floor.



Distributed by:

| PACKAGING | |
|-----------|-----------------------|
| 404760 | 275-gallon totes |
| 404755 | 55-gallon drum |
| 404730 | 30-gallon drum |
| 404715 | 15-gallon drum |
| 404705 | 5-gallon pail |
| 404704 | 1-gallon (4 per case) |



This product meets the Green Seal™ Standard for Floor-Care Products for Industrial and Institutional Use, GS-40, based on its reduced human and aquatic toxicity and reduced smog production potential.

Label copy is available in English, Spanish, and French. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Product Available Worldwide. For institutional and industrial use only.

© SCC 6/12 L4047