



Pro-Shine

high speed floor finish

Pro-Shine is 22% solids, high gloss acrylic emulsion modified with urethane finish for use with high speed-buffers. Its movability and ease of repair are achieved through use of pressure emulsified polyethylene polymers.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
 1110 Spartan Drive
 Maumee, OH 43537
 1-800-537-8990
 www.spartanchemical.com

GLOSS AND DURABLE:

Pro-Shine is a high gloss acrylic emulsion modified with urethane. This finish is extremely durable and movable. Pro-Shine's quick response to high speed equipment substantially reduces the time required for removing black heel marks, scratches, and scuffs from heavily trafficked areas when buffing is employed. The incorporation of a modified urethane adds increased durability without yellowing or discoloring the floor.

EXCELLENT LEVELING:

High solids formulation does not sacrifice leveling. Pro-Shine has excellent flow, applying smooth and even every time.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

Initial Application:

1. Completely strip all old wax or floor finish with a Spartan stripper.
2. Remove the stripping solution and follow with two to three clear water rinses.
3. Apply Pro-Shine in a uniform, thin coat. Let dry for 20 to 30 minutes or until surface is completely dry to the touch. Apply subsequent coats in the same manner.

MAINTENANCE:

1. Dust mop or sweep floors as necessary.
2. Damp mop using a Spartan neutral cleaner.
3. To repair traffic areas between finish applications use a high speed burnisher
4. Deep scrub and recoat or completely strip and refinish as needed.

NOTE: For best results always use Spartan floor cleaners and strippers.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATIONS:

Total Solids – 27.2%
 Non-Volatile Solids – 22%
 pH (Concentrate) – 8.5-9.0

Stability

- a. Storage @24°C/75°F – One year minimum
- b. Accelerated @49°C/120°F – 30 days minimum
- c. Freeze/Thaw – Can withstand three cycles

Gloss (Gardner)

- a. 1 coat – 90
- b. 2 coats – 93



COVERAGE:

Up to 3,000 square feet per gallon depending on application method and porosity of floor.



Distributed by:

PACKAGING	
408260	275-gallon totes
408255	55-gallon drum
408230	30-gallon drum
408215	15-gallon drum
408205	5-gallon pail
408204	1-gallon (4 per case)



Label copy is provided in English, Spanish, and French. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Product Available Worldwide. For institutional and industrial use only.

© SCC 3/11 L4082