



AquaSport[®]

Wood Floor Finish

**one component
water-based urethane**

Spartan's AquaSport Finish is a one-component water-based wood floor finish that utilizes oxygen-cross-linking polyurethane and acrylic chemistry. This urethane-acrylic blend provides easy application, extraordinary performance and strong durability.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, OH 43537
1-800-537-8990
www.spartanchemical.com

PRODUCT FEATURES

AquaSport Wood Floor Finish provides a gloss finish, while enhancing the natural beauty of wood floors. It is applied directly from the container - no mixing, no pot life. AquaSport Wood Floor Finish dries to the touch in approximately 5 hours and reaches full cure in 3-5 days. Quicker re-coat times and faster cure, means your floor can be back in use twice as fast!

RECOMMENDED AREAS FOR APPLICATION

- Sports Floors: MFMA approved for gyms, exercise and aerobic floors, racquetball, handball and squash courts.
- Education: gymnasium, lounges, libraries, offices, and stages.
- Institutional: health care facilities, hospitals, nursing homes, and physicians' offices.
- Commercial: offices, retail sales floors, hotels & motels, restaurants, private clubs, museums.
- Residential: kitchens, entries, great rooms and family rooms.

The low odor formula makes it a good choice for the residential contract industry—especially homes with children and pets.

MEETS VOC EMISSION LEVELS

The extremely low VOC (Volatile Organic Compound) level meets various federal, state and interstate regulations, including the State of California, The Ozone Transport Commission and the Great Lakes Compact. AquaSport Wood Floor Finish is nearly odorless and non-flammable.

EASY APPLICATION

Easy application is achieved with Finish and AquaSport Wood Floor Finish heavy or light weighted T-Bar, such as Padco's "Big Foot Floor Coater", or an on-board tank release type applicator, such as an E-Z Way. Always apply thin coats. Work out puddles and ridge lines.

DIRECTIONS FOR USE

See product label for detailed floor preparation, product application and routine maintenance instructions. Professional technicians or experienced personnel are ideal for fully sanding floors. Floors must be screened to ensure adhesion prior to re-coating. See additional Informative Bulletins for important notes and trouble shooting. Formulated for use on heavy-traffic interior floors.

KEEP OUT OF REACH OF CHILDREN

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATION DATA

Non-Volatile Solids: 25%
Appearance: Light tan
Odor: Resinous odor
Weight Per Gallon: 8.71 lbs.
Flash Point (T.C.C.): > 212°F
VOC content: Less than 275 g/L
Coverage: 600-1000 ft.²/gal.
NOTE: Typical high school basketball court (playing area) is 4,200 ft.² outside court boundaries will add to this significantly.



PACKAGING

582955	55 Gallon Drum
582930	30 Gallon Drum
582915	15 Gallon Drum
582905	5 Gallon Pail
582904	1 Gallon (4 per case)



Distributed by:

Label copy is provided in English and Spanish.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.

For institutional and industrial use only.

© SCC 09/15 L5829