



# AquaSport<sup>®</sup>

## Wood Floor Sanding Seal

**water-based  
wood floor sealer**

Spartan's AquaSport Wood Floor Sanding Seal is a water-based wood floor sealer that provides a base coat for AquaSport Wood Floor Finish and AquaSport 2-Part Wood Floor Finish on new or freshly sanded floors.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.  
1110 Spartan Drive  
Maumee, OH 43537  
1-800-537-8990  
www.spartanchemical.com

### PRODUCT FEATURES

Spartan's AquaSport Wood Floor Sanding Seal provides a foundation to ensure proper adhesion and rapid gloss build of AquaSport waterborne finishes. The formulation minimizes grain raise, tannin bleed and the threat of side bonding. AquaSport Wood Floor Sealer has a light pleasant fragrance, is non-flammable and meets federal and state VOC regulations.

### RAPID FLOOR TURNOVER

AquaSport Wood Floor Sanding Seal exhibits excellent flow and leveling for easy application. It dries and screens to a powder in 2-3 hours, allowing quick access to paint lines and artwork or apply the final finish coats.

### DIRECTIONS FOR USE

Intended for use only on freshly sanded or new natural wood floors.

See product label for detailed floor preparation, product application and routine maintenance instructions. Professional technicians or experienced personnel are necessary for sanding floors. Floors must be screened to ensure adhesion prior to applying paint and finish. See additional Informative Bulletins for important notes and trouble shooting.

**DO NOT FREEZE**  
**KEEP OUT OF REACH OF CHILDREN**

**Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting [www.spartanchemical.com](http://www.spartanchemical.com).**

### SPECIFICATION DATA

**Non-Volatile Solids:** 28%  
**Appearance:** Translucent Emulsion  
**Odor:** Slight ammoniacal odor  
**Weight per gallon:** 8.64 lbs./gal.  
**Flash point (T.C.C.):** > 210°F  
**Coverage:** 400-800 ft.<sup>2</sup>/gal.  
**VOC Content:** < 275 g/L  
**NOTE:** Typical high school basketball court (playing area) is 4,200 ft.<sup>2</sup> outside court boundaries will add to this significantly.



### PACKAGING

<b>583955</b>	55 Gallon Drum
<b>583930</b>	30 Gallon Drum
<b>583915</b>	15 Gallon Drum
<b>583905</b>	5 Gallon Pail
<b>583904</b>	1 Gallon (4 per case)



Distributed by:

**Label copy is provided in English and Spanish.**

**GUARANTEE:** Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.

For institutional and industrial use only.

© SCC 09/15 L5839