



AQUAFORCE[®]

Wood floor finish



Aquaforce wood floor finish is a water-based urethane finish that brings out the natural beauty of sport wood floors. The low-foaming formula provides forgiving leveling and reduced risk of fisheyes, making it an excellent choice for all levels of floor care maintenance experience. The ready-to-use formula requires no mixing, eliminating pot-life concerns. With an amazing high-gloss result and resistance to black heel marks, scuffs, and abrasions, Aquaforce provides the performance characteristics of a 2-part finish with the convenience and ease of a 1-part product.

AQUAFORCE®

FEATURES

- Low-foaming
- Ready-to-use formula
- Low VOCs: available to use in all 50 states
- Easy to apply

BENEFITS

- No mixing required, eliminates pot life concern
- Up to 75% more durable than leading 1-part finishes
- Reduces risk of fisheye during application
- Builds to a high gloss quickly and maintains over time

SPECIFICATION DATA

Dilution	Ready-to-use
pH	7.0 – 8.0
Color	White
Fragrance	Mild
Non-Volatile Solids	28%
VOC Content	< 275 g/L
Coverage	600 – 1000 ft ² /gal
Specific Gravity @ 24°C/75°F	1.037
Flash Point (T.C.C.)	> 100°C / > 212°F ASTM D56

ADDITIONAL RESOURCES

Scan the QR code to access this product's safety information and documentation.




PERFORMANCE

EXCELLENT BLACK HEEL MARK RESISTANCE



Typical 1-Part Finish



AquaForce



Typical 2-Part Finish

EXCELLENT TANNIN BLOCKING



Typical 1-Part Finish



AquaForce



Typical 2-Part Finish

ORDERING INFORMATION



#584304 #584305

SAFETY: For institutional and industrial use only. Be sure to read all directions, precautionary and first aid statements on product labels before using this or any other Spartan product. If questions remain, consult your employer or a physician. Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor and at www.spartanchemical.com. Workplace labels are available in English, Spanish, and French.

GUARANTEE: Spartan's modern manufacturing and laboratory control ensures uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within 12 months of the date of manufacture.