



# Lube-All

**high tech lubricant**

Lube-All, is a high tech lubricant enhanced with ZONYL® PTFE Resin. It maintains longer lubricity and wear resistance. It cleans and lubricates, restoring smooth operation to sticky or rusty mechanisms without disassembling.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.  
1110 Spartan Drive  
Maumee, OH 43537  
1-800-537-8990  
www.spartanchemical.com

#### **PENETRATES AND PROTECTS:**

Quick penetrating action through the smallest cracks and crevices places lubricant where it is needed. Lube All does not dry out and stops irritating squeaks. It protects metals by driving moisture out and providing a barrier against corrosive environments. The rich blend of lubricating oil and anti-friction agents provides a protective barrier against rust and corrosion.

#### **SEVERE CONDITIONS:**

For tough lubrication problems, repeat application. New and Improved Lube-All reaches maximum lubricity within 2 hours after application. To loosen stubborn rust, frozen, or heavily corroded mechanisms, soak overnight.

#### **NUMEROUS APPLICATIONS:**

Use on frozen bolts, fasteners, tools, sliding doors, locks, hinges, window cranks, operating controls, linkages, cables, chains, chucks, dies, electronic gears, etc. Spray on electrical tools, appliances, and automobile starters.

#### **NO CHLORINATED SOLVENTS OR SILICONE:**

Lube-All does not contain chlorinated solvents. The no silicone formula allows protection to ferrous metal parts from flash rusting yet can be removed prior to painting or plating.

#### **DIRECTIONS FOR USE:**

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. If questions remain, consult your employer or a physician.

1. Shake can well before using and occasionally during use.

2. Spray directly on delicate mechanisms, moving parts, machinery, equipment or metal surface to be treated.
3. Coat surfaces thoroughly and allow a few minutes for complete penetration.
4. Once loosened, wipe rust, dirt, and corrosion with a clean cloth.

#### **To loosen rust-frozen and heavily corroded mechanisms:**

Soak in Lube-All overnight. For tough lubrication problems, repeat application. Lube-All reaches maximum lubricity within two-hours after application. Always reapply product at regular intervals to maintain lubricity, protect and extend working life.

#### **WHERE TO SELL:**

Use Lube-All as a preventative maintenance item and a problem solver. Listed below are types of accounts would benefit.

- Locksmiths
- Trucking firms
- Hospitals/nursing homes (all maintenance departments)
- Auto dealers
- Heavy equipment companies
- Aircraft repair shops
- Tool & die shops
- Motorcycle shops
- Hotels/motels
- Schools
- Bowling lanes
- Motor repair shops
- Oil drilling companies
- Office equipment and repair

**Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting [www.spartanchemical.com](http://www.spartanchemical.com).**

\*Zonyl® PTFE Resin is a Registered Trademark of E. I. du Pont de Nemours and Company



Distributed by:

#### **PACKAGING**

673000 20-ounce cans (12 per case)



Label copy is provided in English and Spanish.

**GUARANTEE:** Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.

For institutional and industrial use only.

© SCC 5/11 L6730