



CLEAN ON THE GO[®] DISPENSERS

Dispensing Made Simple[™]



The Clean on the Go dispensers offer employee safety, accurate diluting, and cost-control. Professional products must be used as specified to comply with safety statements and OSHA regulations. Over-proportioned chemicals equal a higher in-use cost, and in order to ensure efficacy against a specified organism, disinfectants must be properly diluted. Available for both bucket and bottle fill applications, Clean on the Go dispensers are designed to work with Spartan's dilution control products. Ensure safety and accuracy with the Spartan Clean on the Go dispensers.

CLEAN ON THE GO® DISPENSERS

KEEP EMPLOYEES SAFE

Maintaining a clean and compliant facility puts your employees and/or contractors on the front lines of your cleaning operations. To minimize liability issues and maximize productivity, the Clean on the Go dispensers make employee safety simple.

- Safety-sealed, closed-system packaging with Clean on the Go
- Color-coded product identification systems
- Customized product usage charts
- Bilingual procedures charts
- Bilingual labeling systems

ACCURATE DILUTION

The Clean on the Go dispensers feature technology to control water pressure and ensure accurate dilution every time.

- Eliminates re-cleaning associated with improperly diluted chemicals
- Ensures proper PPM of actives with disinfectants and sanitizers
- Avoid leaks created with external pressure regulators
- Reduce costs associated with under-diluting chemicals

APPROXIMATE DILUTIONS AT 40 PSI FOR WATER-THIN PRODUCTS (1.0 CPS)

TIP COLOR	ORIFICE SIZE	RATIO	OZ/GAL
Mint Green	0.41mm	1:64	2
Aqua	0.46mm	1:64	2
Orange	0.63mm	1:64	2
Brown	0.58mm	1:64	2
Yellow	0.51mm	1:64	2
Purple	0.36mm	1:256	0.5
Pink	0.25mm	1:256	0.5
Burgundy	0.21mm	1:512	0.25

3-SINK SYSTEM OPTION

Combining two high-flow dispensers, the Clean on the Go 3-Sink System option ensures accurate dilution for sanitizing while controlling cost for manual dish detergent. The 3-Sink System includes everything you need in one box (dispensers, tips, tubing, wall chart, and product identification stickers).

SPECIFICATION DATA

Water Pressure Requirement 15 – 130 psi

For Optimal Performance 30 – 60 psi

Water Temperature Max 160°F/71°C

Flow Rate: Bucket Fill 3.5 – 4.0 gpm

Flow Rate: Bottle Fill 1 gpm

- Air-gap model 99094, 99096 meets plumbing requirement ASSE 1055B and A112.1.2
- Flex-gap model 99093, 99095 meets plumbing requirement ASSE 1055B

ORDERING INFORMATION



#99093 Bottle fill flex-gap #99094 Bottle fill air-gap #99095 Bucket fill flex-gap #99096 Bucket fill air-gap #99132 3-Sink flex-gap #99133 3-Sink air-gap

- #99097 Unit connector
- #99073 Product rack



SAFETY: For institutional and industrial use only. Be sure to read all directions, precautionary and first aid statements on product labels before using this or any other Spartan product. If questions remain, consult your employer or a physician. Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor and at www.spartanchemical.com. Workplace labels are available in English, Spanish, and French.

GUARANTEE: Spartan's modern manufacturing and laboratory control ensures uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within 12 months of the date of manufacture.

www.spartanchemical.com • 1-800-537-8990 • 1110 Spartan Drive, Maumee, OH 43537

© 2021 Spartan Chemical Company, Inc. All Rights Reserved. Clean on the Go is a registered trademark of Spartan Chemical Company, Inc.



03/21 L9909