



Safety Data Sheet

Spartan Chemical Company, Inc.

Revision Date: 29-Jan-2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: CLEAN ON THE GO AIRLIFT TROPICAL [13]
Product Number: 4710
Recommended Use: Air freshener
Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, Ohio 43537 USA
800-537-8990 (Business hours)
www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171
Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion/Irritation: Category 2
Serious Eye Damage/Eye Irritation: Category 1
Skin Sensitization: Category 1
Flammable Liquids: Category 3

GHS Label Elements

Signal Word:

Danger

Symbols:



Hazard Statements:

Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
Flammable liquid and vapor.

Precautionary Statements:

Prevention:

Wash hands and any exposed skin thoroughly after handling.
Wear protective gloves
Wear eye / face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground container and receiving equipment.
Use explosion-proof electrical equipment
Use only non-sparking tools

	Take precautionary measures against static discharge
Response:	
-Eyes	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
-Skin	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.
-Specific Treatment:	See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.
Fire:	In case of fire: Use CO2, dry chemical, or foam for extinction
Storage:	Store in a well-ventilated place. Keep cool
Disposal:	Dispose of contents and container in accordance with local, state and federal regulations.
Hazards Not Otherwise Classified:	Not Applicable
Other Information:	<ul style="list-style-type: none"> • May be harmful if swallowed • Inhalation of vapors or mist may cause respiratory irritation. • Keep out of reach of children

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Water	7732-18-5	30-60
C9-11 Pareth-6	68439-46-3	10-30
Isopropyl Alcohol	67-63-0	5-10
C11-15 Sec-Pareth-12	68131-40-8	3-7
Alkyl C12-16 Dimethylbenzyl Ammonium Chloride	68424-85-1	1-5
Hexylene Glycol	107-41-5	1-5
Fragrance	PROPRIETARY	1-5
Methyldihydrojasmonate	24851-98-7	1-5
Linalool	78-70-6	0.1-1
Hexyl Acetate	142-92-7	0.1-1
Hexamethylindanopyran	1222-05-5	0.1-1
Gamma-Undecalactone	104-67-6	0.1-1
2-T-Butylcyclohexyl Acetate	88-41-5	0.1-1
Benzyl Salicylate	118-58-1	0.1-1
Methylenedioxyphenyl Methylpropanal	1205-17-0	0.1-1
Ethylene Brassylate	105-95-3	0.1-1
Ethyl Linalool	10339-55-6	0.1-1
Citronellol	106-22-9	0.1-1
Benzyl Acetate	140-11-4	0.1-1
3a,4,5,6,7,7a-Hexahydro-4,7-Methano-1H-Indenyl Acetate	54830-99-8	0.1-1
2,6-Dimethyl-7-Octen-2-ol	18479-58-8	0.1-1
Acid Red 52	3520-42-1	<0.1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact:	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
-Skin Contact:	Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical attention.
-Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

-Ingestion: poison control center or physician if you feel unwell.
Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if you feel unwell.

Note to Physicians: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Water spray (fog), Carbon dioxide, Foam, Dry chemical, Water

Specific Hazards Arising from the Chemical: Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Combustion products are toxic.

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Precautions for Firefighters: Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Environmental Precautions: Do not rinse spill onto the ground, into storm sewers or bodies of water.

Methods for Clean-Up: Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Storage Conditions: Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep container tightly closed in a dry and well-ventilated place.

Suggested Shelf Life: Minimum of 2 years from date of manufacture.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
Hexylene Glycol 107-41-5	Ceiling: 25 ppm	(vacated) Ceiling: 25 ppm (vacated) Ceiling: 125 mg/m ³	Ceiling: 25 ppm Ceiling: 125 mg/m ³
Benzyl Acetate 140-11-4	TWA: 10 ppm	-	-

Engineering Controls: Provide good general ventilation.
If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.

Personal Protective Equipment **Eye/Face Protection:** **Skin and Body Protection:** **Respiratory Protection:**

Wear splash goggles.

Wear rubber or other chemical-resistant gloves.

Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a

NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.

General Hygiene Considerations: Wash hands and any exposed skin thoroughly after handling.
See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid
Color:	Pink
Odor:	Tropical floral fragrance
pH:	6.0-7.0
Melting Point / Freezing Point:	No information available
Boiling Point / Boiling Range:	93 °C / 199 °F
Flash Point:	41 °C / 106 °F ASTM D56
Evaporation Rate:	< 1 (Butyl acetate = 1)
Flammability (solid, gas)	No information available
Upper Flammability Limit:	No information available
Lower Flammability Limit:	No information available
Vapor Pressure:	No information available
Vapor Density:	No information available
Specific Gravity:	0.99
Solubility(ies):	Soluble in water
Partition Coefficient:	No information available
Autoignition Temperature:	No information available
Decomposition Temperature:	No information available
Viscosity:	No information available

10. STABILITY AND REACTIVITY

Reactivity: This material is considered to be non-reactive under normal conditions of use.
Chemical Stability: Stable under normal conditions.
Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.
Conditions to Avoid: Extremes of temperature and direct sunlight. Heat, flames and sparks.
Incompatible Materials: Strong oxidizing agents. Strong acids.
Hazardous Decomposition Products: May include carbon monoxide, carbon dioxide (CO₂) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.
Symptoms of Exposure:
-Eye Contact: Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause permanent damage.
-Skin Contact: Pain, redness and cracking of the skin. May cause sensitization by skin contact
-Inhalation: Nasal discomfort and coughing.
-Ingestion: Pain, nausea, vomiting and diarrhea. Ingestion may cause irritation to mucous membranes.
Immediate, Delayed, Chronic Effects
Product Information: Data not available or insufficient for classification.
Target Organ Effects: -Eyes. Respiratory System. -Skin. Central nervous system.
Numerical Measures of Toxicity
The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral):	3547 mg/kg
ATEmix (dermal):	19494 mg/kg
ATEmix (inhalation-dust/mist):	10.8 mg/l
ATEmix (inhalation-vapor):	79 mg/l

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg (Rat)	Not Available	Not Available
C9-11 Pareth-6 68439-46-3	= 1400 mg/kg (Rat)	Not Available	Not Available
Isopropyl Alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
C11-15 Sec-Pareth-12 68131-40-8	= 2100 mg/kg (Rat)	= 2 mL/kg (Rabbit)	Not Available
Alkyl C12-16 Dimethylbenzyl Ammonium Chloride 68424-85-1	= 426 mg/kg (Rat)	Not Available	Not Available
Hexylene Glycol 107-41-5	= 3700 mg/kg (Rat)	Not Available	> 310 mg/m ³ (Rat) 1 h
Methyldihydrojasmonate 24851-98-7	> 5 g/kg (Rat)	Not Available	Not Available
Linalool 78-70-6	= 2790 mg/kg (Rat)	Not Available	Not Available
Hexyl Acetate 142-92-7	= 41500 µL/kg (Rat)	Not Available	Not Available
Hexamethylindanopyran 1222-05-5	> 3250 mg/kg (Rat)	> 3250 mg/kg (Rabbit)	Not Available
Gamma-Undecalactone 104-67-6	= 18500 mg/kg (Rat)	Not Available	Not Available
2-T-Butylcyclohexyl Acetate 88-41-5	= 4600 mg/kg (Rat)	Not Available	Not Available
Benzyl Salicylate 118-58-1	= 2227 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	Not Available
Citronellol 106-22-9	= 3450 mg/kg (Rat)	= 2650 mg/kg (Rabbit)	Not Available
Benzyl Acetate 140-11-4	= 2490 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	Not Available
2,6-Dimethyl-7-Octen-2-ol 18479-58-8	= 3600 mg/kg (Rat)	> 5 g/kg (Rabbit)	Not Available

Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Isopropyl Alcohol 67-63-0	1000: 96 h <i>Desmodesmus subspicatus</i> mg/L EC50 1000: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	9640: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 11130: 96 h <i>Pimephales promelas</i> mg/L LC50 static 1400000: 96 h <i>Lepomis macrochirus</i> µg/L LC50	Not Available	13299: 48 h <i>Daphnia magna</i> mg/L EC50
Hexylene Glycol 107-41-5	Not Available	10500 - 11000: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 10000: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 8690: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 10700: 96 h <i>Pimephales promelas</i> mg/L LC50 static	Not Available	2700 - 3700: 48 h <i>Daphnia magna</i> mg/L EC50
Linalool 78-70-6	88.3: 96 h <i>Desmodesmus subspicatus</i> mg/L EC50	Not Available	Not Available	20: 48 h <i>Daphnia magna</i> mg/L EC50
Hexyl Acetate 142-92-7	Not Available	3.7 - 4.4: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through	Not Available	Not Available

<u>Persistence and Degradability:</u>	No information available.
<u>Bioaccumulation:</u>	No information available.
<u>Other Adverse Effects:</u>	No information available

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes:	Dispose of in accordance with federal, state and local regulations.
Contaminated Packaging:	Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

<u>DOT:</u>	
UN/ID No:	UN1993
Proper Shipping Name:	Flammable liquids, n.o.s., (Isopropanol)
Hazard Class:	3
Packing Group:	III
Special Provisions:	Class 3, Packing Group III materials meet the exception requirements of section 49 CFR 173.150 when individual containers of not more than 1.3 gallons are packed in a strong outer packaging and ground transportation is utilized. Such containers may be reclassified as "Limited Quantity". Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.

<u>IMDG:</u>	
UN/ID No:	UN1993
Proper Shipping Name:	Flammable liquids, n.o.s., (Isopropanol)
Hazard Class:	3
Packing Group:	III

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product contains the following listed substances:

SARA 311/312 Hazard Categories

Acute Health Hazard:	Yes
Chronic Health Hazard:	No
Fire Hazard:	Yes
Sudden release of pressure hazard:	No
Reactive Hazard:	No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards: 2	Flammability: 2	Instability: 0	Special: N/A
<u>HMIS</u>	Health Hazards: 2*	Flammability: 2	Physical Hazards: 0	

Revision Date:	29-Jan-2022
Reasons for Revision:	Section, 2, 4, and, 11

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet