

# Safety Data Sheet Spartan Chemical Company, Inc.

**1. PRODUCT AND COMPANY IDENTIFICATION** 

Product Identifier Product Name: Product Number: Recommended Use: Uses Advised Against:	<b>CARBON &amp; GREASE REMOVER (AEROSOL)</b> 6281 Cleaning agent For Industrial and Institutional Use Only
Manufacturer/Supplier:	Spartan Chemical Company, Inc. 1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com
24 Hour Emergency Phone Number Medical Emergency/Information: Transportation/Spill/Leak:	rs: 888-314-6171 CHEMTREC 800-424-9300
	2. HAZARDS IDENTIFICATION
<b>GHS Classification</b> Skin Corrosion/Irritation: Serious Eye Damage/Eye Irritation: Flammable Aerosols	Category 1 Sub-category B Category 1 Category 1
<u>GHS Label Elements</u> Signal Word: Symbols:	Danger
Hazard Statements:	Causes severe skin burns and serious eye damage. Extremely flammable aerosol.
Precautionary Statements: Prevention:	Do not breathe mist, vapors or spray. Wash hands and any exposed skin thoroughly after handling. Wear protective gloves. Wear eye / face protection. Wear protective clothing. Keep away from heat/sparks/open flames/hot surfaces. — No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use
Response:	IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
-Eyes	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
-Skin	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse.
-Inhalation:	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for
-Ingestion: -Specific Treatment:	breathing. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

lavage.

Storage:	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 $^\circ F$
Disposal:	Dispose of contents and container in accordance with local, state and federal regulations.
Hazards Not Otherwise Classified:	Not Applicable
Other Information:	<ul> <li>Corrosive</li> <li>May be harmful if swallowed</li> <li>Harmful contact may not cause immediate pain.</li> <li>Inhalation of vapors or mist may cause respiratory irritation or damage.</li> <li>Keep out of reach of children</li> <li>NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric</li> </ul>

# **3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%
Water	7732-18-5	60-100
Butoxydiglycol	112-34-5	7-13
Sodium Hydroxide	1310-73-2	7-13
Butane	106-97-8	1-5
Propane	74-98-6	1-5
Xanthan Gum	11138-66-2	0.1-1
Rheology Additive	PROPRIETARY	0.1-1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES		
-Eye Contact:	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.	
-Skin Contact:	Take off immediately all contaminated clothing and shoes. Rinse with water or shower for at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash contaminated clothing before reuse. Discard or destroy contaminated shoes.	
-Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.	
-Ingestion:	Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Never give anything by mouth to an unconscious person.	
Note to Physicians:	NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.	
5. FIRE-FIGHTING MEASURES		

Suitable Extinguishing Media:	Water spray, fog or regular foam.
Specific Hazards Arising from the	Extremely flammable aerosol. Exposure to high temperature may cause containers to burst.
Chemical:	Bursting aerosol containers may be propelled from fire at high speed.
Hazardous Combustion Products:	May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.
Protective Equipment and Precautions for Firefighters:	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat.

# 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.
Environmental Precautions:	Do not rinse spill onto the ground, into storm sewers or bodies of water.
Methods for Clean-Up:	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with
	non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite)

and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE		
Advice on Safe Handling:	Handle in accordance with good industrial hygiene and safety practice. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Wash thoroughly after	
Storage Conditions:	handling. NFPA 30B Level 1 Aerosol. Do not store in direct sunlight or above 122 F° / 50 C°. Exposure to high temperature may cause containers to burst. Keep out of the reach of	
Incompatible Materials:	children. Strong acids. Oxidizing agents.	

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

TWA: 10 ppm inhalable fraction and vapor         Ceiling: 2 mg/m³         STEL: 1000 ppm         : See Appendix F: Minimal Oxygen Content         Provide good general ventilation If work practices generate dust chemicals above the occupation	t, fumes, gas, vapors or mists w	
STEL: 1000 ppm SEE Appendix F: Minimal Oxygen Content Provide good general ventilation If work practices generate dust	(vacated) Ceiling: 2 mg/m <sup>3</sup> (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup> TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> on.	Ceiling: 2 mg/m <sup>3</sup> TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup> IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
See Appendix F: Minimal Oxygen Content Provide good general ventilation If work practices generate dust	(vacated) TWA: 1900 mg/m <sup>3</sup> TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> on.	TWA: 1900 mg/m <sup>3</sup> IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
Oxygen Content Provide good general ventilation If work practices generate dust	TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> on. t, fumes, gas, vapors or mists w	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
If work practices generate dust	t, fumes, gas, vapors or mists w	
engineering controls should be	considered.	
Wear splash goggles. For severe use-conditions, wear a face shield over the goggles. Wear rubber or other chemical-resistant gloves. Use of impervious apron, boots and other protective equipment should be considered in order to prevent or minimize contact with this product.		
Not required with expected use If occupational exposure limits NIOSH/MSHA approved respir 3 should be considered.	are exceeded or respiratory irri ator suitable for the use-conditi	
	Eye wash stations and shower product is handled. Wear splash goggles. For seve Wear rubber or other chemical protective equipment should be product. Not required with expected use If occupational exposure limits NIOSH/MSHA approved respir 3 should be considered. Wash hands and any exposed	Eye wash stations and shower facilities should be readily accepted on the product is handled. Wear splash goggles. For severe use-conditions, wear a face Wear rubber or other chemical-resistant gloves. Use of imperproduct of the product. Not required with expected use. If occupational exposure limits are exceeded or respiratory irr NIOSH/MSHA approved respirator suitable for the use-conditional exposure limits are exceeded or respiratory in the use-conditional exposure limits are exceeded or respiratory in the use-conditional exposure limits are exceeded or the use-con

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid
Color:	Beige
Odor:	Mild glycol ether odor
pH:	12.5-14
Melting Point / Freezing Point:	No information available
Boiling Point / Boiling Range:	140 °C / 284 °F
Flash Point:	-104 °C / -155 °F
Evaporation Rate:	No information available
Flammability (solid, gas)	No information available
Upper Flammability Limit:	No information available
Lower Flammability Limit:	No information available
Vapor Pressure:	No information available
Vapor Density:	No information available
Specific Gravity:	1.07 (Product without propellant)
Solubility(ies):	Miscible in water
Partition Coefficient:	No information available
Autoignition Temperature:	No information available
Decomposition Temperature:	No information available
Viscosity:	No information available

# **10. STABILITY AND REACTIVITY**

Reactivity:	This material is considered to be non-reactive under normal conditions of use.
Chemical Stability:	Stable under normal conditions.
Possibility of Hazardous Reactions:	Not expected to occur with normal handling and storage.
Conditions to Avoid:	Extremes of temperature and direct sunlight.
Incompatible Materials:	Strong acids. Oxidizing agents.
Hazardous Decomposition	May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.
Products:	

## **11. TOXICOLOGICAL INFORMATION**

Likely Routes of Exposure: Symptoms of Exposure:	Eyes, Skin, Ingestion, Inhalation.
-Eye Contact:	Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause permanent damage.
-Skin Contact:	Pain, redness, blistering and possible chemical burn.
-Inhalation:	Irritation or damage to the mucus membranes of the respiratory tract. Nasal discomfort and coughing.
-Ingestion:	Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and diarrhea.
Immediate, Delayed, Chronic Effec	ts
Product Information:	Data not available or insufficient for classification.
Target Organ Effects: Numerical Measures of Toxicity	Central nervous systemEyes. Respiratory SystemSkin.
The following acute toxicity estimates	(ATE) are calculated based on the GHS document.
ATEmix (oral):	4561 mg/kg

		3.3
ATEmix (dermal):	8741	mg/kg

### Component Acute Toxicity Information

Chemical Name	Chemical Name Oral LD50		Inhalation LC50	
Water 7732-18-5	> 90 mL/kg (Rat)	Not Available	Not Available	
Butoxydiglycol 112-34-5	= 5660 mg/kg (Rat)	= 2700 mg/kg (Rabbit)	Not Available	
Sodium Hydroxide 1310-73-2	Not Available	= 1350 mg/kg (Rabbit)	Not Available	
Butane	Not Available	Not Available	= 658 g/m <sup>3</sup> (Rat) 4 h	

106-97-8			
Propane	Not Available	Not Available	= 658 mg/L (Rat)4 h
74-98-6			

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or **OSHA** 

## **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to	Crustacea
			Microorganisms	
Butoxydiglycol 112-34-5	100: 96 h Desmodesmus subspicatus mg/L EC50	1300: 96 h Lepomis macrochirus mg/L LC50 static	Not Available	100: 48 h Daphnia magna mg/L EC50
Sodium Hydroxide 1310-73-2	Not Available	45.4: 96 h Oncorhynchus mykiss mg/L LC50 static	Not Available	Not Available

#### Persistence and Degradability: Bioaccumulation:

No information available. No information available.

Other Adverse Effects:

No information available

## **13. DISPOSAL CONSIDERATIONS**

**Disposal of Wastes: Contaminated Packaging:**  Dispose of in accordance with federal, state and local regulations. Pressurized container: Do not pierce or burn, even after use. Dispose of in accordance with federal, state and local regulations.

## **14. TRANSPORT INFORMATION**

DOT:	
UN/ID No:	UN1950
Proper Shipping Name:	Aerosols, flammable
Hazard Class:	2.1
Subsidiary Class:	8
Special Provisions:	This aerosol product meets the exception requirements of 49 CFR 173.306 when packed in strong outer packaging. Such material may be reclassified as "Limited Quantity".
IMDG:	
UN/ID No:	UN1950
Proper Shipping Name:	Aerosols, Flammable
Hazard Class:	2.1
Subsidiary hazard class	8

## **15. REGULATORY INFORMATION**

**TSCA Status:** (Toxic Substance Control Act Section 8(b) Inventory) All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

#### **SARA 313**

This product contains the following listed substances:

# Butoxydiglycol

CAS No 112-34-5 applies to R-(OCH2CH2)n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or SulfonateChemical Category N230

SARA 311/312 Hazard Categories	
Acute Health Hazard:	Yes
Chronic Health Hazard:	No
Fire Hazard:	No
Sudden release of pressure hazard:	Yes

#### Reactive Hazard:

No

#### California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION					
NFPA HMIS	Health Hazards: 3 Health Hazards: 3	Flammability: Flammability:		Instability: 0 Physical Hazards: 2	Special: N/A
Revision Date: Reasons for Revision:	01-Dec-2023 New product				

**Disclaimer:** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**