



Revision Date: 11-Mar-2021

User-Prepared Solution Safety Summary Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: **XTREME TIRE AND WHEEL CLEANER USER PREPARED SOLUTION (1:10)**
Diluted at 1:10 (or greater) in water

Manufacturer/Supplier: Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, Ohio 43537 USA
800-537-8990 (Business hours)
www.spartanchemical.com

Medical Emergency/Information: 888-314-6171

2. HAZARDS IDENTIFICATION

GHS Classification
Skin Corrosion/Irritation: Category 1
Serious Eye Damage/Eye Irritation: Category 1

GHS Label Elements

Signal Word:

Danger

Symbols:



Hazard Statements: Causes severe skin burns and serious eye damage.

Precautionary Statements:

Prevention:

Do not breathe mist, vapors or spray.

Wash hands and any exposed skin thoroughly after handling.

Wear protective gloves. Wear eye / face protection. Wear protective clothing.

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

Response:

-Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

-Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse.

-Inhalation:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

-Ingestion:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

-Specific Treatment:

See Safety Summary Sheet Section 4: "First Aid Measures" for additional information.

Storage:

Store locked up.

Disposal:

Dispose of contents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: Not Applicable

Other Information:

Corrosive. Harmful if swallowed. Harmful contact may not cause immediate pain. Inhalation of vapors or mist may cause respiratory irritation. Keep out of reach of children. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Water	7732-18-5	90-100
Butoxyethanol	111-76-2	0.1-1.0
C9-11 Pareth-6	68439-46-3	0.1-1.0
Sodium Silicate	1344-09-8	0.1-1.0
PEG-15 Cocomonium Chloride	61791-10-4	0.1-1.0
Potassium Hydroxide	1310-58-3	0.1-1.0
Trisodium Dicarboxymethyl Alaninate	164462-16-2	0.1-1.0
Undeceth-3	34398-01-1	0-0.1
Lauramine Oxide	1643-20-5	0-0.1

4. FIRST AID MEASURES

- Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
- Skin Contact:** Take off immediately all contaminated clothing and shoes. Rinse with water or shower for at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash contaminated clothing before reuse.
- Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
- Ingestion:** Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Never give anything by mouth to an unconscious person.
- Note to Physicians:** NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

5. PERSONAL PROTECTIVE EQUIPMENT (PPE)

- Eye/Face Protection:** Wear splash goggles. For severe use-conditions, wear a face shield over the goggles.
- Skin and Body Protection:** Wear rubber or other chemical-resistant gloves. Use of impervious apron, boots and other protective equipment should be considered in order to prevent or minimize contact with this product.
- Respiratory Protection:** Not required with expected use.
If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.
- General Hygiene Considerations:** Wash hands and any exposed skin thoroughly after handling. See 29 CFR 1910.132-138 for further guidance.

6. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Clear
Odor:	solvent
pH:	12.3-13.3
Flash Point:	> 100 °C / > 212 °F ASTM D56
Specific Gravity:	1.01

7. OTHER INFORMATION

NFPA Health Hazards: 3 **Flammability:** 0 **Instability:** 0 **Special:** N/A
HMIS Health Hazards: 3 **Flammability:** 0 **Physical Hazards:** 0

Revision Date: 11-Mar-2021
Reasons for Revision: First edition